# University of California, Berkeley Physics 105 Fall 2000 Section 1 (Strovink)

#### ASSIGNMENT 12

## Reading:

105 Notes 14.6 Hand & Finch 10.1-10.2

#### 1.

Consider a uniform cube of side L. Inside the cube is a scalar field  $\phi$  that satisfies the wave equation with characteristic wavespeed c. At the surfaces of the cube,  $\phi$  is required to vanish.

 $(\mathbf{a})$ 

Show that for this system the total number of modes of vibration corresponding to frequencies between  $\nu$  and  $\nu + d\nu$  is  $4\pi L^3 \nu^2 d\nu/c^3$ , if  $\pi c/L \ll d\nu \ll \nu$ .

**(b)** 

What would the result be for a (two-dimensional) square?

 $(\mathbf{c})$ 

A (one-dimensional) rod?

## **2.** and **3.** (double credit problem)

Consider a homogeneous isotropic solid medium, i.e. a medium that, unlike a liquid, is able to resist being twisted (it "supports a shear stress"). The Lagrangian density for such a medium is

$$\mathcal{L}' = \frac{1}{2} \rho \frac{\partial u_i}{\partial t} \frac{\partial u_i}{\partial t} - \frac{1}{2} \frac{\partial u_i}{\partial x_j} C_{ijkl} \frac{\partial u_k}{\partial x_l} ,$$

where summation over repeated indices is (definitely!) implied. In this expression, the field variables are  $u_1(x_1, x_2, x_3, t)$ ,  $u_2(x_1, x_2, x_3, t)$ , and  $u_3(x_1, x_2, x_3, t)$ . These describe the (vector) displacement  $\mathbf{u}$  of a small element of the solid from its equilibrium position  $\mathbf{x}$ . (The *strain* is obtained by taking spatial derivatives of  $\mathbf{u}$ .) The mass density of the solid is  $\rho$ , which for small values of  $\mathbf{u}$  can be approximated as a constant.  $C_{ijkl}$  is the "fourth-rank tensor of elasticity".

Exploiting the homogeneous medium's isotropy, one can show that the most general form for  $C_{ijkl}$  is

$$C_{ijkl} = \lambda \delta_{ij} \delta_{kl} + \mu (\delta_{ik} \delta_{jl} + \delta_{il} \delta_{jk}) ,$$

where  $\lambda$  and  $\mu$ , the so-called "Lamé constants", determine all 81 of its elements. The inverse of the compression modulus  $\lambda$  is proportional to the compressibility of the medium, and the inverse of the shear modulus  $\mu$  is proportional to the extent to which the medium can be twisted.

Notice that the Lagrangian density for a solid medium could in principle depend on 19 variables (3 field variables,  $3 \times 4$  derivatives of 3 field variables with respect to 4 independent variables, and 4 independent variables). In practice, our Lagrangian density has no dependence on the first and last category, so it is a function of only 12 variables.

Use the Euler-Lagrange equations for this Lagrangian density to derive the wave equations for compression waves  $(\nabla \times \mathbf{u} = 0)$  and for shear waves  $(\nabla \cdot \mathbf{u} = 0)$  in the solid. Obtain the phase velocity c for both cases, in terms of  $\lambda$ ,  $\mu$ , and  $\rho$ . Notice that an earthquake can propagate with more than one velocity!

#### 4.

Consider an infinitely long continuous string in which the tension is  $\tau$ . A mass M is attached to the string at x=0. If a sinusoidal wave train with velocity  $\omega/k$  is incident from the left, analyze the reflection and transmission that occur at x=0. Define the reflection coefficient  $R\equiv |\mathcal{R}|^2$  and the transmission coefficient  $T\equiv |\mathcal{T}|^2$ , where  $\mathcal{R}$  and  $\mathcal{T}$  are the reflected and transmitted amplitude ratios discussed in Lecture Notes section 14.6.

Show that R and T are given by  $R = \sin^2 \theta$  and  $T = \cos^2 \theta$ , where  $\tan \theta = M\omega^2/2k\tau$ . [Hint: Consider carefully the boundary condition on the derivatives of the wave functions at x = 0.]

# ${\bf 5.}$ Hand & Finch, Problem 10.1 (stability in a central force)

**6.** Hand & Finch, p. 397,  $Question\ 6$  (upside-down pendulum)

7. and 8. (double credit problem) Hand & Finch, Problem 10.9 (a)-(d) only (how does a child pump a swing?)